

Made-To-Measure Form Uniform Pants

			www.scoutshop.org
Name:		Date:	
Shipping Address:			
Day Time Phone Number:			Email:
For Office Use Only Order Number:		PO Number:	For Office Use Only
Pant Fabric/Style: Comments: Micropoly			
For more accurate measurements, lay your garment FLAT on a HARD surface and use a soft measuring tape. Smooth the garment with your hands, but do not stretch the fabric. Ironing is recommended for garments that are highly wrinkled. Note: For optimum results, consult a professional tailor to take these garment measurements.			
Fill out this section if you're able to find an existing in-stock pant size that are an optimal fit and only require alterations to the inseam length. Simply follow these easy steps for requesting pants modifications: 1) Try on pants and record SKU# below of style that fits best. 2) Measure current inseam length of pants and record below. 3) Indicate the new requested hemmed inseam below. Record the requested hemmed inseam in section G. 4) In section G, subtract the difference between the Current BSA Stock Item Inseam and the Customer Requested Inseam (even if it is an unhemmed measurement). Enter this measurement on the Difference line.			
SKU: Description:			
G. Inseam Length (From top of inseam to bottom of the pant) Current BSA Stock Item Inseam: Difference (+-):		inches Requested Inse	eam: inches
MADE-TO-MEASURE REQUEST			
	the garment (do not use surements. Refer to the or Height:	e jeans) with your hands, but	•
All measurements should be based on actual garments. Not body measurements.			
A. Waist: x 2: *This measurement will not correspond to the size on the label. Please take this measurement from the garment label as directed below. From side to side and double this measurement. Do not stretch elastic if any is present. B. Hip: x 2: From 8" below waistband, measure from side to side. Double this measurement.	C. Inseam: Hemmed Un-Hemmed - F actual inseam me D. Thigh:	From the crotch to pant edge. asurement to account for hem x 2: parallel to the leg opening, 1" b	Add 2" to ming) E. Bottom Leg Opening: Y x 2: Starting at the bottom of the pant leg opening. Double this measurement. F. Front Rise: Starting at the bottom of the waistband, measure along the front zinger and scare to the interpretion of the inseam
		FRONT	BACK RISE

Diagram B

Diagram A